

IN THE CLAIMS

Please amend the claims to read as follows:

1. (Currently Amended) An encoder comprising:
an epoch locator coupled to a frame assembly,
a primary epoch analyzer coupled to the epoch locator, and
a secondary epoch analyzer coupled to the primary epoch locator,
wherein the encoder compresses a plurality of signals at variable frame rates
based on a plurality of prioritized epoch parameters to dynamically reduce signal
bandwidth while preserving perceptual signal quality, wherein said prioritized
epoch parameters are reduced based on each of said plurality of epoch data
parameters respective priority.
2. (Original) The apparatus of claim 1, wherein a transmission rate of the
plurality of compressed signals is dynamically set.
3. (Original) The apparatus of claim 1, wherein the plurality of compressed
signals are speech signals.
4. (Original) The apparatus of claim 1, wherein the encoder comprises:
an epoch locator unit;
a first epoch analyzer;
a second epoch analyzer; and
a frame assembler unit.
5. (Original) The apparatus of claim 4, wherein the plurality of compressed
signals in one of half frames and full frames.

6. (Original) The apparatus of claim 4, further including a network traffic manager coupled to the encoder.
7. (Original) The apparatus of claim 6, wherein the network manager is one of co-resident with the encoder and remotely located relative to the encoder.
8. (Currently Amended) The apparatus of claim 1, wherein a priority level of each of the plurality of prioritized epoch parameters is based on quality of speech.
9. (Currently Amended) A decoder comprising:
 - a frame disassembly and parameter decoding unit coupled to an excitation generator;
 - a synthesizing filter coupled to the excitation generator; and
 - an output scaling and filtering unit coupled to the synthesizing filter,wherein the decoder decompresses a plurality of compressed signals at variable frame rates based on a plurality of prioritized epoch parameters to dynamically reduce signal bandwidth while preserving perceptual signal quality, wherein said prioritized epoch parameters are reduced based on each of said plurality of epoch data parameters respective priority.
10. (Original) The apparatus of claim 9, wherein a transmission rate of the plurality of compressed signals is dynamically set.
11. (Original) The apparatus of claim 9, wherein the plurality of compressed signals are speech signals.
12. (Original) The apparatus of claim 9, wherein the decoder comprises:
 - a frame disassembly and parameter decoding unit;
 - an excitation generator;
 - a synthesizing filter; and
 - an output scaling and filtering unit.

05313P002
09/759,734

-3-

SL/lmd

13. (Currently Amended) The apparatus of claim 9, wherein the plurality of compressed signals decompressed by the decoder at variable rates based on the plurality of prioritized epoch parameters improve transmission during dynamically changing bandwidth while preserving perceptual quality of the signals.

14. (Currently Amended) A program storage device readable by a machine comprising instructions that cause the machine to:

- receive a plurality of signals from a first transmission device;
- encode the plurality of signals in a compressed format; and
- transmit the plurality of signals in a compressed format through a transmission medium at variable frame rates based on a plurality of prioritized epoch parameters to dynamically reduce signal bandwidth while preserving perceptual quality of the signals, wherein said prioritized epoch parameters are reduced based on each of said plurality of epoch data parameters respective priority.

15. (Original) The program storage device of claim 14, wherein a transmission rate of the plurality of compressed signals is dynamically set.

16. (Original) The program storage device of claim 14, wherein the plurality of signals in a compressed format are speech signals.

17. (Original) The program storage device of claim 14, wherein encode instructions cause the machine to:

- locate an epoch;
- analyze a first epoch;
- analyze a second epoch; and
- assemble a frame.

18. (Original) The program storage device of claim 17, wherein the transmit of the plurality of compressed signals is in one of a half frame and a full frame.

19. (Currently Amended) The program storage device of claim 14, further comprising instructions that cause the machine to:
- prioritize each of the plurality of prioritized epoch parameters based on quality of speech.
20. (Currently Amended) A program storage device readable by a machine comprising instructions that cause the machine to:
- receive the plurality of signals in a compressed format through a transmission medium at variable rates based on a plurality of prioritized epoch parameters to reduce signal bandwidth while preserving perceptual quality of the signals;
 - decode the plurality of compressed signals; and
 - transmit the decoded signals to a first receiving device,
 - wherein said prioritized epoch parameters are reduced based on each of said plurality of epoch data parameters respective priority.
21. (Original) The program storage device of claim 20, wherein a transmission rate of the plurality of compressed signals is dynamically set.
22. (Original) The program storage device of claim 20, wherein the plurality of signals in a compressed format are speech signals.
23. (Original) The program storage device of claim 20, wherein decode instructions cause the machine to:
- disassemble and parameter decode a frame;
 - generate an excitation;
 - synthesize and filter; and
 - scale and filter an output.

24. (Currently Amended) The program storage device of claim 20, wherein the receipt of the plurality of compressed signals at variable rates based on the plurality of prioritized epoch parameters improves signal transmission during dynamically changing bandwidth of the transmission medium while preserving perceptual quality of the signals.

25. (Currently Amended) The program storage device of claim 20, further comprising instructions that cause the machine to:
prioritize each of the plurality of prioritized epoch parameters based on quality of speech.

26. (Currently Amended) A method comprising:
receiving a plurality of signals from a transmission device;
encoding the plurality of signals in a compressed format; and
transmitting the plurality of signals in a compressed format through a transmission medium at variable rates based on a plurality of prioritized epoch parameters to reduce signal bandwidth while preserving perceptual quality of the signals.

wherein said prioritized epoch parameters are reduced based on each of said plurality of epoch data parameters respective priority.

27. (Original) The method of claim 26, wherein the variable transmission rate of the plurality of compressed signals is dynamically set.

28. (Original) The method of claim 26, wherein the plurality of signals in a compressed format are speech signals.

29. (Original) The method of claim 26, wherein encoding comprises:
locating an epoch;
analyzing a first epoch;
analyzing a second epoch; and

05313P002
09/759,734

assembling a frame.

30. (Original) The method of claim 26, wherein the transmitting of the plurality of compressed signals is in one of a half frame and a full frame.

31. (Currently Amended) The method of claim 26, further comprising:
establishing a priority level of each of the plurality of prioritized epoch parameters based on quality of speech.

32. (Currently Amended) The method of claim 26, wherein the transmitting of the plurality of compressed signals at variable rates based on the plurality of prioritized epoch parameters improves signal transmission during dynamically changing bandwidth of the transmission medium while preserving perceptual quality of the signals.

33. (Currently Amended) A method comprising:
receiving a plurality of signals in a compressed format through a transmission medium at variable rates based on a plurality of prioritized epoch parameters to reduce signal bandwidth while preserving perceptual quality of the plurality of the signals;
decoding the plurality of compressed signals; and
transmitting the decoded signals to a receiving device,
wherein said prioritized epoch parameters are reduced based on each of said plurality of epoch data parameters respective priority.

34. (Original) The method of claim 33, wherein the variable transmission rate of the plurality of compressed signals is dynamically set.

35. (Original) The method of claim 33, wherein the plurality of signals in a compressed format are speech signals.

36. (Original) The method of claim 33, wherein decoding comprises:
disassembling and parameter decoding a frame;
generating an excitation;
synthesizing and filtering; and
scaling and filtering an output.
37. (Currently Amended) The method of claim 33, wherein the receiving the plurality of compressed signals at variable rates based on the plurality of prioritized epoch parameters improves signal transmission during dynamically changing bandwidth of the transmission medium while preserving perceptual quality of the signals.
38. (Original) The method of claim 33, wherein the receiving of the plurality of compressed signals is in one of a half frame and a full frame.
39. (Currently Amended) The method of claim 33, wherein receiving comprises:
prioritizing each of the plurality of prioritized epoch parameters based on quality of speech.
40. (Currently Amended) An apparatus comprising:
means for encoding a plurality of input signals at variable frame rates, the
means for encoding including:
means for identifying input signal segments;
means for extracting a plurality of epoch parameters describing signal segments; and
means for associating priority values to the plurality of epoch parameters.
41. (Currently Amended) The apparatus of claim 40, wherein the means for encoding comprises compressing the plurality of input signals at variable frame

rates based on the plurality of prioritized epoch parameters to dynamically reduce signal bandwidth while preserving perceptual signal quality.

42. (Currently Amended) An apparatus comprising:
means for decoding a plurality of compressed signals;
the decoding means including:
 means for reconstructing parameters from the plurality of compressed signals;
 means for constructing an excitation signal;
 means for producing a raw output signal; and
 means for producing a final output signal,
 wherein the means for decoding comprises decompressing the plurality of compressed signals at variable frame rates based on a plurality of prioritized epoch parameters to dynamically reduce signal bandwidth while preserving perceptual signal quality.

43. (Cancelled).